

ALINCO

Quality. Style. Performance!

VHF/UHF FM HANDHELD TRANSCEIVERS

DJ-A10 136~174MHz

DJ-A40 400~470MHz




Rugged, Reliable Radio That Withstands Your Demands... at an affordable price!

These VHF/UHF handheld transceivers pack a lot of performance into a MIL-spec* rugged polycarbonate bodies. Designed to resist splash and dust*, the DJ-A10/A40 features professional grade specs such as 1W audio output, 2.5ppm frequency stability, capable of operating at 5W with 50 tone-squelch, DCS or DTMF/ANI in 128 programmable-channels or VFO; keep in touch for retails, construction, factory, warehouse, in a theme-park, shopping mall, exhibition hall, hotel...where you need reliable communications for business, the DJ-A10/A40 is a cost effective alternative to a mobile/cell phone!

*MIL-STD-810G shock/vibration compliant

*IP54 Dust & Splash-proof compatible



VHF DJ-A10
UHF DJ-A40



MIL-STD-810G Compliant
-Shock: Method 514.6/1,IV
-Vibration: Method 516.6/1



Performance Doesn't Have to Cost More!

Features

- 128 channels to program operating parameters via PC utility software
- Channel, Name tag and VFO (Frequency) display modes selectable
- Comes with a rechargeable Li-Ion pack, desktop quick-charger and high-performance whip antenna
- Ergonomically designed compact body 59.0W x 98.0H x 35.0D mm or 2.32W x 3.86H x 1.38D inches (w/o projections, approx.), weighs approx.227g or 8.01oz inclusive of battery pack and antenna
- 3 types of Scan functions (VFO/Memory channels/Priority), 50 CTCSS, 116 DCS and 4 Tone-burst tones
- Backlit, Dot Matrix LCD screen with alphanumeric name tag
- Microphone and speaker ports
- Includes FM radio receiver, Internal VOX, Voice-prompt in English, Remote-Kill/Stun/Revive, Analog scrambling, Voice compander, Narrow FM, Repeater-reverse, Auto-Power-off, Busy-Channel-Lockout, Time-Out-Timer and more and more at No extra cost!

*IP54 rating classification

5 : Dust protected /Ingress of dust is not entirely prevented, but it must not enter in sufficient quantity to interfere with the satisfactory operation of the equipment; complete protection against contact
4: Splashing water / Water splashing against the enclosure from any direction shall have no harmful effect. Test duration: 5 minutes / Water volume: 10 litres per minute /Pressure: 80-100 kN/m²



shown with EBP-87

Specifications

General

- Frequency coverage : [DJ-A10] 136-174MHz [DJ-A40] 400-470MHz
- Mode : F3E(16K0F3E / 11K0F3E / RX only WFM)
- Programmable channels : 128 channels
- Frequency stability : ±2.5ppm
- Power supply requirement : 7.4V DC±20% (negative ground)
- Current drain (Approx.) : 1400mA TX / 300mA receive at Max audio output / 70 mA squelched
- Usable temperature range : -20~ +55°C(-4~131°F)
- Dimensions (Projections not included/approx.) : 59.0W×98.0H×35.0D mm or 2.32W×3.86H×1.38D inches
- Weight : approx.227g or 8.01oz inclusive of battery pack and antenna

Transmitter (ETSI EN300 086 compliant)

- Output power : Approx. [A10] 5 / 2 / 0.5W [A40] 4 / 2 / 0.5W
- Modulation system : Variable reactance FM
- Spurious emissions : Less than -36dBm
- Max. frequency deviation : ±5kHz / ±2.5kHz

Receiver (ETSI EN300 086 compliant)

- Receive system : Double conversion superheterodyne
- Intermediate frequencies : [A10] 38.85MHz / [A40] 26.45MHz
- Sensitivity(12dB SINAD Wide/Narrow) : -12dBμ or better (0.25μV/0.35μV) or better
- Selectivity : -6dB : Wide 12kHz /Narrow 10kHz or more -60dB : Wide 30kHz / Narrow 24kHz or less
- Audio output power : 1000mW(10% distortion)

Standard Accessories

(A strap is included)

Whip antenna	Battery Pack	
	A10/40 version	A10/40 T/E version
A10 : EA-211	EBP-88	EBP-87
A40 : EA-212	Li-ion 7.4V 1700mAh	Li-ion 7.4V 1500mAh

Rapid ChargerStand	AC Adapter	Belt Clip
EDC-189	A10/40: EDC-190E A10/40T: EDC-191T A10/40E: EDC-191E	EBC-34

Standard accessories declared herein are our factory default and may vary at moment of sales depending on the market and Dealers' sales policy.

The AC adapter shown here is EDC-190E.



Shown with standard accessories

Options



- Earphone Microphone (EME-56A)
- Mobile DC charging cable (EDC-198)

※ Voids IP54 ingress protection when EME-56A and/or EDH-40 are in use.



- Mobile DC cable (EDH-40)



Specifications and contents on this brochure subject to change without notice or obligation. Cellular frequencies blocked.

Authorized Dealer:

ALINCO FRANCE
www.alinco.fr



Please be sure to read the instruction manual before using the product for your safety.

Copyright Alinco, Inc., Osaka, Japan. All rights reserved. Although Alinco has designed this brochure to be as accurate and comprehensive as possible, we reserve the right to make changes at any time to our equipment line, optional accessories, specifications, standard accessories, or availability of any such devices we manufacture and distribute. Please note that certain products and accessories may not be available in all countries of distribution therefore consult your Authorized Alinco Dealer for product availability and pricing. Specifications apply only to ham bands unless otherwise specified. Colors of images herein may appear slightly different from actual products due to print.
* Projections are not included in the declared dimension values.
* FCC and CE logos in this brochure mean that these products have been approved under the business-radio category of relative conformity unless otherwise specified.

ALINCO, INC. Electronics Division

Yodoyabashi Dai-Bldg 13F, 4-4-9 Koraibashi,
Chuo-ku, Osaka 541-0043 Japan
Phone: 06-7636-2362 Fax: 06-6208-3802
<http://www.ALINCO.com>
E-mail: export@alinco.co.jp

FNFNEGNI-PE
Ver.1.0 A10A40
Printed in Japan